



GRIP^{line} R34

PROFESSIONAL FRAME

- Rim clamping up to 34"
- Automatic tire leverless system, for disassembling and reassembling
- Double arm/disk air operated bead breaker system
- Reinforced chassis and tower
- Patented ultra -quick wheel clamping system, through cone and shaft with lock nut
- Double rotation speed INVERTER system
- Standard equipped with slide lift
- Bead pressing arm complete with self-storage function
- Locking system for total stiff locking of horizontal and operating arm



Made in Italy 

PRODUCT NUMBER / DESCRIPTION

6040 GRIP R34
Power supply: single-phase
220v - 50/60Hz

DATASHEET



Working pressure
8 - 10 bar



Rim clamping
range 10" - 34"



Max tire width 16"
(406 mm)



Maximum tire diameter
1200 mm



Rotation speed
7 - 16 rpm



Weight 395 kg



Dimensions (H x D x L)
2300 x 1888 x 1980 mm



Cardboard box packaging (H x D x L)
1880 x 1150 x 1420 mm


STANDARD ACCESSORIES



n. 2 rubber protection
for clamping chuck



Plastic tire lever



n. 3 demounting head
tongue protection



n. 3 mounting tool cover



Bead pressing device



n. 2 plastic protection for
lock nut centering cone

EXTRA OPTIONS FOR TIRE CHANGERS GRIP R34



ART. 6227

- Kit of 10 rubber protection for clamping chuck



ART. 6228

- Plastic protection for lock nut centering cone set of 10



ART. 6229

- Plastic tire lever. To be used during tire demanding in accordance with the WDK procedure



ART. 6230

- Kit of four rubber protection for alloy wheels with exposed spokes



ART. 6231

- Nylon cone for special LAMBORGHINI wheels, center hole diameter from Ø 55 - 85 mm




ART. 6232

- Nylon cone for special PORSCHE wheels, allows clamping wheels with center hole diameter from Ø 60 to 85 mm.



ART. 6233

- Nylon cone for special BMW wheels, allows clamping wheels with center hole diameter from Ø 55 to 70 mm.



ART. 6234

- Double face cone for light trucks, allows clamping VANs and LCVs wheels with center hole diameter from 75 to 145 mm.



ART. 6235

- Truck cone kit, allows clamping VANs and LCVs wheels with center hole diameter from 120 to 190 mm.




ART. 6236

- Truck cone kit, allows clamping VANs and LCVs wheels with center hole diameter from 190 to 223 mm.



ART. 6237

- Wheel clamping adaptor for reverse mounted wheels and wheels with no center hole



ART. 6238

- Cone for steel rims with low thickness and center hole diameter from 75 to 120 mm



ART. 6240

- Kit of 10 mounting tool cover for GRIP R34



ART. 6241

- Kit of 10 demounting head tongue protection for GRIP R34



ART. 6239

- Inflating tubeless kit



ART. 6244

- Higher bead pressing device



ART. 6245

- Bead pressing device



ART. 6247

- Adjusting device for leverless tools GRIP R34