

GRIP^{line} SUPER52

- Hydraulic spindle with double speed and double rotation.
- Hydraulic fitting carriage sliding
- Adjustable hydraulic pressure.
- Four clamping jaws for precise gripping.
- Jaw clamp fast rotation. Manual tightening.
- Bead breaking force 26500 N

DATASHEET



Spindle tightening
• inward 14"-40"
• up to 56" with ART.7054



Tire width
max 1150 mm



Maximum tire diameter
2300 mm



Rotation speed
4,5 - 9 rpm



Weight 880 kg



Dimensions (H x D x L)
1750 x 2150 x 2500 mm



Cardboard box packaging (H x D x L)
1025 x 2250 x 1950 mm



Made in Italy 

PRODUCT NUMBER / DESCRIPTION

7005 GRIP SUPER 52
Power supply: 3-phase
400v - 50/60Hz

STANDARD ACCESSORIES



- Mounting lever 500 mm
- Long mounting lever
- Rim clamp for aluminum rims

EXTRA OPTIONS FOR TIRE CHANGERS GRIP SUPER 52




ART. 7052

- Protective jaws for aluminium rims, set of 4



ART. 7054

- Clamping extension jaw, set of 4



ART. 7057

- Rims adaptors kit. Central hole 80 mm



ART. 7055

- Rim clamp for aluminum rims



ART. 7050

- Inflation cage for truck tires

INFLATION CAGE FEATURES

Weight 166 kg

External dimensions (H x D x L)
1580 x 1600 x 800 mm

Internal dimensions (H x D x L)
1500 x 1500 x 700 mm

Maximum tire diameter
1500 mm

Maximum tire width
700 mm