

GRIP^{line} SUPER56

- Hydraulic spindle with double speed and double rotation.
- Hydraulic fitting carriage sliding.
- Adjustable hydraulic pressure.
- Six patented clamping jaws for a precise gripping. Suitable for different positions.
- Bead breaking fast rotation with pneumatic system
- Bead breaking force 26500 N

DATASHEET



Spindle tightening inward 14" - 56"



Tire width max 1300 mm



Maximum tire diameter 2300 mm



Rotation speed 4,5 - 9 rpm



Weight 1000 kg



Dimensions (H x D x L) 1750 x 2150 x 2500 mm



Cardboard box packaging (H x D x L) 1025 x 2250 x 1950 mm



Made in Italy 

The picture shows
CODE GRIP Super 52

PRODUCT NUMBER / DESCRIPTION

7010	GRIP SUPER 56 Power supply: 3-phase 400v - 50/60 Hz
-------------	--

STANDARD ACCESSORIES



- Mounting lever 500 mm
- Long mounting lever
- Rim clamp for aluminum rims

EXTRA OPTIONS FOR TIRE CHANGERS GRIP SUPER 56



ART. 7051

- Protective jaws for aluminium rims, set of 6



ART. 7053

- Clamping extension jaw, set of 6



ART. 7055

- Rim clamp for aluminum rims



ART. 7050

- Inflation cage for truck tires

INFLATION CAGE FEATURES

Weight 166 kg

External dimensions (H x D x L)
1580 x 1600 x 800 mm

Internal dimensions (H x D x L)
1500 x 1500 x 700 mm

Maximum tire diameter
1500 mm

Maximum tire width
700 mm