



ROLLline R8 TRUCK

- TFT Monitor showing programs
- 5 specific programs for truck wheels
- Internal electronic measuring arm for rim distance & diameter
- Standard pneumatic lift for wheel-mounting
- Threaded screw 40 mm
- Automatic balancing speed based on wheel weight

INSTALLATION VIDEO

INSTRUCTIONS AVAILABLE NOW!



Made in Italy 🇮🇹

PRODUCT NUMBER / DESCRIPTION

8050	ROLL R8 TRUCK Power supply: single-phase 220v - 50/60Hz
-------------	--

DATASHEET



Accuracy
1 gr car - 10 gr truck



Working pressure
8 - 12 bar



Tire width
min 1" - max 24"



Tire diameter
min 6" - max 40"



Rotation speed
100/200 rpm



Max wheel weight
200 kg



Weight 310 kg



Dimensions (H x D x L)
1870 x 1270 x 2040 mm



Cardboard box packaging (H x D x L)
1210 x 950 x 1900 mm

STANDARD ACCESSORIES



- Threaded screw with block 40 mm
 - Quick nut
- 4 cones from 43 to 110 mm



- Truck precision flange with 4- and 5-arm centring system



- Weight pliers
- Calibration weight
- Weights removal blade
- Weight sample

EXTRA OPTIONS FOR WHEEL BALANCER ROLL R8 TRUCK




ART. 8204

- Precision bush kit from 52,5 to 122 mm of 9



ART. 8205

- 3-4-5 hole flange



ART. 8210

- Lockring cap



ART. 7050

- Inflation cage for truck tires

INFLATION CAGE FEATURES

Weight 166 kg

External dimensions (H x D x L)
1580 x 1600 x 800 mm

Internal dimensions (H x D x L)
1500 x 1500 x 700 mm

Maximum tire diameter
1500 mm

Maximum tire width
700 mm